

usignolo



Volt 230/50 1-ph

usignolo dry



Volt 230/50 1-ph

	I-Gal		HP	l./min.-CFM		Bar-Psi	dB/A	cm AxBxC inch.		Kg - Lbs	cm AxBxC inch.		Kg - Lbs	dryer	
usignolo	24-6,34	1	0,75	100-4	62-2,3	8-114	70	40x47x70	16x16x28	28-62	85x70x100	33x28x39	40-88	no	1
usignolo dry	24-6,34	1	0,75	100-4	62-2,3	8-114	70	40x60x70	16x24x28	38-84	85x70x100	33x28x39	50-110	yes	1

(*) @ 5 bar (70PSI)

rondine



Volt 230/50 1-ph
220/60 1-ph
115/60 1-ph

rondine dry



Volt 230/50 1-ph
220/60 1-ph
115/60 1-ph

	I-Gal		HP	l./min.-CFM		Bar-Psi	dB/A	cm AxBxC inch.		Kg - Lbs	cm AxBxC inch.		Kg - Lbs	dryer	
rondine	24-6,34	2	1,5	150-6,4	121-4,7	8-114	72	40x47x70	16x16x28	31-68	85x70x100	33x27x39	45-99	no	1
rondine dry	24-6,34	2	1,5	150-6,4	121-4,7	8-114	72	40x60x70	16x24x28	41-90	85x70x100	33x27x39	55-121	yes	1

(*) @ 5 bar (70PSI)